

SMART SHUTTER PLATFORM

ONE MOTION PLATFORM. UNLIMITED SOLUTIONS.

Focus & Shutter Platform



The M3-RS platform delivers fast, precise, and reliable optical control in a compact, low-power, fully integrated module.



FAST

70ms Shutter




ZERO POWER HOLD

No holding current




PRECISE

Closed-loop position control for optimal performance



QUIET

No solenoid kick
No bounce
No noise



INTEGRATED

3.3v operation with internal controller and drivers

SMART OPTICAL CONTROL

The NST Smart Shutter provides advanced capabilities over standard actuators

- Programmable Optical States, not limited to open/closed positions
- Optical Sub-System, simplified integration
- Software Defined Behaviour, soft close, adjustable speed & acceleration
- Multi-Function Capabilities

BUILT FOR SWaP

Small, Lightweight, Efficient, Reliable.

Designed for the **most** demanding missions.

Key Performance Metrics

Actuation Type	Rotary
Move Time (90°)	70 ms Typical
Position Accuracy	±0.25°
Repeatability	±0.05°
Input Voltage	3.3V
Operating Power	750 mW
Holding Power	0 mW
Interface	SPI/ I2C / UART
Mass	5 g
Dimensions	21.9 x 11.75 x 16 mm



EO/IR CAMERAS



DEFENSE SYSTEMS



MEDICAL & SCIENTIFIC INSTRUMENTS




UAV/UGV PAYLOADS



INDUSTRIAL INSPECTION




Smart Shutter Dimensions




Blade Options

- Matte Black Anodized Aluminum
- Carbon Fiber



Smart Shutter Platform

Rotation Range	360° Continuous Rotation
Speed	> 1,100°/s
Acceleration	> 1,000,000°/s
Stall Torque (min)	0.04 N-mm
Holding Torque (max)	0.08 N-mm (no power)
Stage Mass	5 g
Payload	
Mass	3 g
Inertia	350 g-mm ²
Closed Loop Performance	
Step Frequency	100 Hz
Resolution	22 mdeg (14 bit)
Repeatability	± 0.05°
Accuracy	0.25°
Step & Settle Times	
0.5°	16 ms
5°	22 ms
20°	31 ms
Electrical & Control	
Input Voltage	3.3VDC
Power	750 mw moving 0 mw stationary
Communication Interface	I2C, SPI, UART
Controller	Integrated 64 MIPS controller



NST Pathway™ Application

The included Pathway software provides access to stage settings, scripted motion commands, diagnostics, and more with an easy to use graphical interface.

ASCII commands can be sent directly to stages using the Manual Command Entry or you can create your own code using the intuitive scripting tool.

